

SPORTGATE EPSA/DPSA

Hexta developed the sportgate especially for sport facilities in field fencing with double bar mat. By applying double rod filling, the sportgate has the same appearance as the field fence. In addition, the upper girder of the wing of the sports gate harmonizes with the railing of the fencing, so that the gate and gate form a smooth line. The wings of the gates have a full border of welded box section. The gates have been built for years of use and have an excellent price-quality ratio.



TECHNICAL SPECIFICATIONS

SPORTGATE EPSA/DPSA WIDTH

- EPS 125 cm / DPS 250 cm

HEIGHT

- DPS 100 - 110 -120 cm

VLEUGELS

- Frame of box section 50 x 50 x 2 mm in which a double rod mat is welded with horizontal wires \varnothing 8mm and vertical wire \varnothing 6mm with a mesh size of 50 x 200 mm.
- Wings by spindle hinges hung on gate posts, ensuring good adjustability

POORTPALEN

- Round poles that are driven into the ground about 80 cm deep.
- Gate posts 89 by 125 and 150 single; 250 and 300 double.
- Gate posts 108 by 200 single; 400 double. (See schedule below)

SLUITING

- Day and night lock with handle lock and euro profile cylinder

CONSERVATION

- Galvanized according to NEN-en-ISO 1461.
- Option: an additional coating can be applied according to the duplex system to beautify and extend the service life.

STANDARD COLORS

- Green (RAL 6009)
- Black (RAL 9005)

SUBSTANDARD COLORS

- Green (RAL 6020, RAL 6005)
- Blue (RAL 5011),
- White (RAL 9010)
- Other colors on request

SINGLE GATE

WIDTH	GATEPOLE	HEIGHT
125	Ø 89	100
150	Ø 89	110
200	Ø 108	120

DOUBLE GATE

WIDTH	GATEPOLE	HEIGHT
250	Ø 89	100
300	Ø 89	110
400	Ø 108	120