

VELDAGE SEPARATION SAV

A fence that forms a functional partition between players and spectators. The uprights and handrail are coupled by means of a special head, which is secured by use of a bayonet connection and is optimally secured. For better stability and to facilitate mowing, a galvanized steel cutting plate with adjusting ring is fitted.



TECHNICAL SPECIFICATIONS

VELDAGE SEPARATION SAV

UPRIGHTS

- Ø60.3 x 1.75 mm, centerpoint 3 meters and about 80 cm into the ground.
Options:
- Centerpoint 2 or 2.50 meters - special cover plate for paving

HANDRAIL

- Ø41.5 x 2 mm coupled to the uprights by a special feedthrough head with bayonet fitting for an optimal connection.
- Height of choice: 90, 110 or 120 cm

OPTIONS

- Extra tensioning with mesh mat 50 x 50 x 3 or 3.7 mm
- Extra tensioning with a double bar mat, mesh size 50 x 200 mm, wire thickness 2 x Ø8 / 1 x Ø6 mm
- A galvanized steel cutter plate secured with an adjusting ring
- Billboard provision

Opening

- chain which is attached between 2 end posts

Corner / end posts

- Extra stands and special brackets

CONSERVATION

- Galvanized according to NEN-en-ISO 1461
- Option: an additional coating can be applied according to the duplex system to beautify and extend the lifespan

OPTIONS

- Green, (RAL 6009) Black (RAL 9005) (standard)
- Green (RAL 6020, RAL 6005) and Black (RAL 9005) (substandard)
- Other colors on request

